

TOPTHERM CLEAN 1

SPECIFIC PRODUCT FOR CLEANING WITH ZERO DRAIN AND FOR USING WITH T-MAG AND MAG CLEANER MAGNETIC FILTERS. FOR HIGH TEMPERATURE HEATING AND CONDITIONING SYSTEMS.

Description

TOPTHERM CLEAN 1 removes metal oxides from radiators and pipes, by taking them in suspension in water. It penetrates them and lift them into circulation, carrying them to the T-MAG and MAG CLEANER magnetic filters, which allows their removal. The product does not modify pH, it does not contain E.D.T.A. and it does not corrode metals nor plastics. It does not contain toxic nor harmful substances. It does not remove incrustations, residues of welds or flakes.

- It does ask any powerflushing or draining.
- It cleans without the risk of causing losses.
- It is compatible with all metals, including aluminium.
- It is compatible with the biocide TOPTHERM BIOCID.
- It is compatible with the inhibitor TOPTHERM PROTECT 1.
-

How to use

Add **TOPTHERM CLEAN 1** to the system with the inhibitor **PROTECT 1**.

Recommended usage: 0,5 kg of **TOPTHERM CLEAN 1** every 100 litres of water.

Lower concentrations do no yield satisfactory results. The product can be left inside the system with the T-MAG and MAG CLEANER magnetic filters without powerflushing or draining it. For low temperature systems or mixed, it is suggested to add the biocide/bactericide **TOPTHERM BIOCID**.

Physical and chemical properties:

Aspect: amber liquid
pH solution 0,5%: about 6 - 7

Environmental and safety information

TOPTHERM CLEAN 1 it is not classified as hazardous substance. Do not allow the product to reach potable waters. Do not ingest. Do not dispose of waste through the environment. For more details about a safe manipulation and storage of the product, refer to TOPTHERM CLEAN 1 MSDS.

Available package

0,5 and 1 kg bottles –2 and 5 kg cans